

Limits

Menu Format




# Residential Combustion Analyzer Fyrite® INSIGHT® Plus



Vibrant, full-colordisplayshows easy-to-readreal-time analysis

Fast and accurate O<sub>2</sub>, CO (0-4,000 ppm), T-stack/air temperature nddraft/pressure neasurements

- 9 pre-programmed ser-selectable uels (+2 custom)
- Printstoreddata(100 records)anddatadownload via USB with Fyrite User Software





As easy as 1-2-3: Select fuel type, select appliance type and then start analysis.

The Fyrite INSIGHT Plus is Bacharach's premiumes idential and light commercial combustion analyzer. This American-madanalyzeruses advanced technology to accurately measure, analyze and report results that validates afe operation efficiently tune oldersystems and save customers' money.

Featuring industry-exclusive-Smart COsensor technology, tenable stechnicians and HVAC/R service representatives to install pre-calibrate densors right in the field to avoid costly down time and inconvenience.

#### Five Tools in ONE with Real-Time Analysis

The Fyrite INSIGHT Plus is a five-in-onesteady state combustion analyzer that is capable of measuring fluegas and roomair CO, and can also functions a dual channel digital thermomete (up to 999°F) and a digital manomete (which measures draft, gas pressure, ESP, and up to +/- 40 INWC).

Able to provide up to 100 combustion pressure and temperature ecords, the Fyrite INSIGHT Plus can also can display measurement esults instantly for up to ten different fuels on its full-color backlit LCD display. In additions pecific information also be downloaded on PC or printed via an infrared printer.









## Fyrite INSIGHT Plus Features & Benefits:

Five tools in ONE!

- · Combustionandefficiency analyzer
- Room air COtest instrument
- · Flue gas COtester
- · Dual channeldigitalthermometer
- · Digital manometer

Full-Color Graphic LCD display

 Vibrant colorscreendisplayseasyto-readreal-timegraphs, status and analysis results.

User diagnostics

- O<sub>2</sub> sensorlife indication
- Calibrationreminders

Reporting package (optional)

- Customizetest reportswith your companylogo
- Upload customfuels
- Software updates

Pre-calibrated B-Smart CO sensor with integral NOx filter

Manual Zero/Auto-Zero (CO) feature New! High CO Shut-Off/Protection feature New! 2-year or 3-year C<sub>2</sub> sensor warranty



The B-Smart Sensor Exchange Programallows users to replace pre-calibrated ensors in the field, eliminating the need to send the instrument for calibration With the B-Smart Sensor Exchange Program, you receive factory-calibrated sensors, just plug the min and continue to use your instrument – there's no down time and it saves time and money.

### Fyrite INSIGHT Plus Specifications

9 User-Selectable Fuels: NaturalGas, Oil #2, Oil #4, Oil #6, Propane,Coal,Wood, Kerosene,B5 (+ 2 custom)| (10 fuels available with Siegertver)

Measurement Ranges: CombustiorAir/AmbientAir -4 to 600° F (-20 to 316° C)

Temperature

FlueGas Temperature -4 to 1,202° F (-20 to 650° C)

 $\begin{array}{ll} \text{Oxygen(O}_2) & 0.0 \text{ to } 20.9\% \\ \text{CarbonMonoxide(CO)} & 0 \text{ to } 4,000 \text{ ppm} \end{array}$ 

Draft/ DifferentiaPressure -40 to +40 INWC (100 mBar)

Calculated Ranges: CombustionEfficiency 0.1 to 100%

CarbonDioxide(CO<sub>2</sub>)
0.1 to a fuel dependent max. value in percent

CarbonMonoxide(air free) 0 to 9,999 ppm Excess Air 0 to 250%

Dimensions: 8.0"H x 3.6"W x 2.3"D (20.3 cm x 9.1 cm x 5.8 cm)

Weight: 16 oz. with batteries(0.45 kg)

Power: 4 AA Alkalinebatteries(incl.), Universalpoweradapteror USB cable

Minimumof 15 hourstypicalbatterylife

Warranty: Instrumentandsensors - 2 years includin  $\mathfrak{O}_2$  sensor

Long-life0<sub>2</sub> sensorcarries a 3-yearwarranty

Approvals: EN 50270 (CE mark), EN 50379

Contents:

Display Languages Available: English, French, Spanish, Polish, German, Italian, Dutch, Danish

Fyrite\* INSIGHT\* Plus: instrumentomes with probe, spare filters, protective ubberboot, 4 AA batteries, user manual and

hardcarryingcase.

Fyrite\* INSIGHT\* Plus w/Reporting Pkg. Kit: instrumentomes with probe, spare filters, protective ubbehoot, IrDA printer USB cable, Fyrite\* User Software, 8 AA batteries, hardcarrying case

#### Fyrite INSIGHT Plus Ordering Information

0024-8515	Fyrite INSIGHT Plus
0024-8517	Fyrite INSIGHT Plus (with Long-LifeO2 sensor)
0024-8519	Fyrite INSIGHT Plus - EuropearModel*
0024-8521	Fyrite INSIGHT Plus EuropearModel*(with Long-LifeO2 sensor)
0024-8516	Fyrite INSIGHT Plus w/Reporting Kg Kit
0024-8518	Fyrite INSIGHT Plus w/Reporting kg Kit (with Long-Life) sensor)
0024-8520	Fyrite INSIGHT Plus w/Reporting Kg Kit – Europear Model*
0024-8522	Fyrite <sup>®</sup> INSIGHT <sup>®</sup> Plus w/Reporting <sup>®</sup> kg Kit – EuropearModel*(w/Long-Lif <sub>®</sub> 2 sensor)
	*Furonean based calculations

### Fyrite INSIGHT Plus Accessories

	0024-1492	*FMREGHT" Plus ReportingKit (with IrDA printer, USB cable & software)
	0024-1400	P <b>łriDt∕e</b> rw/Disposabl <b>∉</b> AA) BatteriesandMagnet
	0024-1310	Präupteen (5 rolls)
	0024-1611	Uni <b>ନ</b> େଞ୍ଚ <b>ା</b> werAdapter
	0104-1797	Thermo <b>to (t</b> p(eombustionat temp.)
ı	0104-1798	Thermo <b>ն տալ փե</b> enbien tair temp.)
i	0024-8242	Diffe <b>Peetsial</b> re& Temperatur <b>e</b> Kit
i	0024-1591	Lor@g-RefplacemenSensor
	0024-1593	Sencor(notcalibrated)
ı	0024-1616	B-S6Qastensor(pre-calibrated)
	0024-8257	Long-LifeO₂ SensorUpgradeKit
1		



